The content of this SDS is also valid in Spanish Mexican language to cover all Central America, South America (except Brazil) and the Caribbean countries.

# SAFETY DATA SHEET



Texwipe® Sterile 70% Denatured Ethanol (16 Oz, 32 Oz, 128 Oz)

### **Section 1. Identification**

GHS product identifier : Texwipe® Sterile 70% Denatured Ethanol (16 Oz, 32 Oz, 128 Oz)

**Product code** : TX3267, TX3265, TX3291

Product type : Liquid.

#### **Identified uses**

For use in various cleaning applications.

Supplier/Manufacturer : Texwipe

1210 South Park Drive Kernersville, NC 27284

Tel: 1-(336) 996-7046 (Toll Free: 1-(800) 839-9473)

Fax: 1-(336) 996-6563 Web: www.texwipe.com

Emergency telephone number (with hours of operation) : CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3887

### Section 2. Hazards identification

**OSHA/HCS status** 

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

**GHS** label elements

Hazard pictograms





Signal word : Danger

**Hazard statements** : H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

**Precautionary statements** 

**General** 

: Read label before use. Keep out of reach of children. If medical advice is needed, have

product container or label at hand.



#### Section 2. Hazards identification

Prevention

: P280 - Wear protective gloves. Wear eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling

equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P233 - Keep container tightly closed.

P271 - Use only outdoors or in a well-ventilated area.

P261 - Avoid breathing vapor.

P264 - Wash hands thoroughly after handling.

Response

: P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER or physician if you feel unwell.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water or shower.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.

Storage : P405 - Store locked up.

P403 - Store in a well-ventilated place.

P235 - Keep cool.

**Disposal** P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

#### **Hazards not otherwise classified (HNOC)**

Physical hazards not otherwise classified

(PHNOC)

**Health hazards not** otherwise classified

(HHNOC)

: None known.

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

#### CAS number/other identifiers

**CAS** number : Not applicable.

**Product code** TX3267, TX3265, TX3291

Ingredient name	%	CAS number
	60 - 75 3 - 5	64-17-5 67-63-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact**: Flush contaminated skin with plenty of water. Get medical attention if symptoms occur.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention

immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt

or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact**: No known significant effects or critical hazards.

Ingestion : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.



### Section 4. First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet or water-based fire extinguishers.

Specific hazards arising from the chemical

: Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

**Special protective actions for fire-fighters** 

Special protective equipment for fire-fighters

- : Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.



### Section 6. Accidental release measures

#### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating. drinking and smoking. See also Section 8 for additional information on hygiene measures.

### including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **United States**

#### Occupational exposure limits

Ingredient name	Exposure limits
Ethyl Alcohol	ACGIH TLV (United States, 3/2015).  STEL: 1000 ppm 15 minutes.  NIOSH REL (United States, 10/2013).  TWA: 1900 mg/m³ 10 hours.
	TWA: 1000 ppm 10 hours.  OSHA PEL (United States, 2/2013).  TWA: 1900 mg/m³ 8 hours.  TWA: 1000 ppm 8 hours.
Isopropyl alcohol	ACGIH TLV (United States, 3/2015).  STEL: 400 ppm 15 minutes.  TWA: 200 ppm 8 hours.  NIOSH REL (United States, 10/2013).
	STEL: 1225 mg/m³ 15 minutes. STEL: 500 ppm 15 minutes. TWA: 980 mg/m³ 10 hours.



### Section 8. Exposure controls/personal protection

TWA: 400 ppm 10 hours. **OSHA PEL (United States, 2/2013).**TWA: 980 mg/m³ 8 hours.

TWA: 400 ppm 8 hours.

#### Canada

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)		Ceiling					
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Ethyl Alcohol	US ACGIH 3/2015 AB 4/2009 BC 5/2015 ON 7/2015 QC 1/2014 SK	- 1000 - - 1000 -	- 1880 - - 1880 -	- - - - 1000 PPM	1000 - 1000 1000 - -	- - - -	- - - - - 1250 PPM	- - - -	- - - -	- - - -	
Isopropyl alcohol	US ACGIH 3/2015 AB 4/2009 BC 5/2015 ON 7/2015 QC 1/2014 SK	200 200 200 200 400 -	- 492 - - - 983 -	- - - - 200 PPM	400 400 400 400 500	- 984 - - 1230 -	- - - - - 400 PPM	- - - -	- - - -	- - - -	

#### <u>Mexico</u>

Ingredient name	Exposure limits
Ethyl Alcohol	NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 1900 mg/m³ 8 hours. LMPE-PPT: 1000 ppm 8 hours.
Isopropyl alcohol	NOM-010-STPS (Mexico, 9/2000).  LMPE-CT: 1225 mg/m³ 15 minutes.  LMPE-CT: 500 ppm 15 minutes.  LMPE-PPT: 980 mg/m³ 8 hours.  LMPE-PPT: 400 ppm 8 hours.

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**





### Section 8. Exposure controls/personal protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.

Color : Not available.

Odor : Not available.

Odor threshold : Not available.

pH : Not available.

Melting point : Not available.

Boiling point : >80°C (>176°F)

Flash point : Closed cup: 21°C (69.8°F) [Pensky-Martens.]

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Partition coefficient: n-: Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Volatility : Not available.

VOC (w/w) : 71.4 % (w/w)





### Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethyl Alcohol	LC50 Inhalation Vapor			4 hours
	LD50 Oral		7 g/kg	-
Isopropyl alcohol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl Alcohol	Eyes - Moderate irritant	Rabbit	-	100 µL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	_
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	_
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes	-
				100 mg	
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
Isopropyl alcohol	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	10 mg	-

#### **Sensitization**

There is no data available.

#### Carcinogenicity

#### Classification

Product/ingredient name	OSHA	IARC	NTP	<b>ACGIH</b>	EPA	NIOSH
Isopropyl alcohol Ethyl Alcohol	None. -	3 -	-	A4 -	-	- -

#### Specific target organ toxicity (single exposure)

Name	<b>y</b>	Route of exposure	Target organs
Texwipe® Sterile 70% Denatured Ethanol (16 Oz, 32 Oz, 128 Oz) Ethyl Alcohol Isopropyl alcohol	Category 3	Not applicable.	Narcotic effects Narcotic effects Narcotic effects





### Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

There is no data available.

#### **Aspiration hazard**

There is no data available.

Information on the likely

routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact**: No known significant effects or critical hazards.

**Ingestion**: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering

**Inhalation** : Adverse symptoms may include the following:

redness

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

: No known significant effects or critical hazards.

effects

**Potential delayed effects**: No known significant effects or critical hazards.

Long term exposure

**Potential immediate** : No known significant effects or critical hazards.

effects

**Potential delayed effects**: No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 





### **Section 11. Toxicological information**

There is no data available.

### **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Ethyl Alcohol	Acute EC50 17.921 mg/L Marine water Acute EC50 2000 μg/L Fresh water Acute LC50 25500 μg/L Marine water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae	96 hours 48 hours 48 hours
Isopropyl alcohol	Acute LC50 42000 μg/L Fresh water Chronic NOEC 4.995 mg/L Marine water Chronic NOEC 0.375 ul/L Fresh water Acute LC50 1400000 to 1950000 μg/L Marine water Acute LC50 4200 mg/L Fresh water	Fish - Oncorhynchus mykiss Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae Crustaceans - Crangon crangon Fish - Rasbora heteromorpha	4 days 96 hours 12 weeks 48 hours 96 hours

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Ethyl Alcohol	-0.35	-	low
Isopropyl alcohol	0.05		low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



## **Section 14. Transport information**

	DOT	TDG / NOM-003-SCT	IMDG	IATA
UN number	UN1987	UN1987	UN1987	UN1987
UN proper shipping name	ALCOHOLS, N.O.S. (Ethyl Alcohol, Isopropyl alcohol)		ALCOHOLS, N.O.S. (Ethyl Alcohol, Isopropyl alcohol)	ALCOHOLS, N.O.S. (Ethyl Alcohol, Isopropyl alcohol)
Transport hazard class(es)	3	3	3	3
Packing group	II	II	II	II
Environmental hazards	No.	No.	No.	No.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).	-	-

**AERG** : 127

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

: Not available.

### **Section 15. Regulatory information**

U.S. Federal regulations

: United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602

**Class I Substances** 

: Not listed

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** (Precursor Chemicals) : Not listed

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

**SARA 304 RQ** 

: Not applicable.

**SARA 311/312** 





### Section 15. Regulatory information

Classification : Fire hazard

Immediate (acute) health hazard

#### Composition/information on ingredients

Name	%	hazard	Sudden release of pressure		(acute) health	Delayed (chronic) health hazard
Ethyl Alcohol Isopropyl alcohol		Yes. Yes.	-	No. No.	Yes. Yes.	No. No.

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	Isopropyl alcohol	67-63-0	3 - 5
Supplier notification	Isopropyl alcohol	67-63-0	3 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **State regulations**

Massachusetts : The following components are listed: Ethyl Alcohol; Isopropyl alcohol

**New York** : None of the components are listed.

New Jersey : The following components are listed: Ethyl Alcohol; Isopropyl alcohol Pennsylvania : The following components are listed: Ethyl Alcohol; Isopropyl alcohol

California Prop. 65

No products were found.

#### **Canada**

**Canadian lists** 

Canadian NPRI : The following components are listed: Ethyl Alcohol; Isopropyl alcohol

CEPA Toxic substances : None of the components are listed.Canada inventory : All components are listed or exempted.

**International lists** 

**National inventory** 

Australia : All components are listed or exempted.
China : All components are listed or exempted.
Europe : All components are listed or exempted.

Japan : Japan inventory (ENCS): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

Malaysia: All components are listed or exempted.New Zealand: All components are listed or exempted.Philippines: All components are listed or exempted.Republic of Korea: All components are listed or exempted.Taiwan: All components are listed or exempted.



### Section 16. Other information

#### **History**

Date of issue mm/dd/yyyy : 08/15/2016

Date of previous issue : 02/15/2016

Version : 5

Prepared by : KMK Regulatory Services Inc.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.